



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

CAPACITY

PRICE

| | |
|----------|---------|
| 300 L | £2,700 |
| 500 L | £3,400 |
| 1000 L | £4,300 |
| 1500 L | £5,100 |
| 2000 L | £5,500 |
| 3000 L | £7,200 |
| 4000 L | £7,900 |
| 5000 L | £9,000 |
| 10,000 L | £13,900 |
| 20,000 L | £24,000 |

Indicative price only
Does not include shipping

SPECIFICATION

Inner-Jacket (SUS304), TH=3.0mm
 External-Jacket(SUS304), TH=2.0mm
 Dish head (SUS304), TH=3.0mm
 Dish head on top and bottom of tank
 Insulation: PU-thickness: 80mm
 Glycol jacket: dimpled plate placed on side
 CIP arm with cleaning ball
 PVRV and pressure gauge placed on the CIP arm
 Two-way pressure relief valve placed on the top of tank
 Side manway: 280*380mm
 Sampling port with full sanitary sample valve
 With carbonation stone
 With liquid level sight tube
 With Ladder hook and Lifting lug
 With glycol water inlet and outlet
 Design pressure 0.3Mpa
 Working pressure (without PED Certificate) 0.049Mpa
 PED certification available on request